



0550

Protector Transport Case

With over 11 cubic feet (0.311 cubic meters) of space, you can store, protect, and move large loads in seconds. The reinforced honeycomb deck and lid construction provide support for heavy equipment, or multiple stacking on a 463L pallet. Opening the case at any altitude is not a problem- the dual integrated automatic pressure equalization valves keep moisture out and prevent vacuum lock, and the double wide grip makes lifting easy. With an IP55 certification, the 0550 Transport Case will protect your gear against rain and dirt. The 0550 Transport Case: Built to move-by forklift, by wheel, by hand.

- Over 11ft³ (.311m³) of storage space
- Fit six 0550 Cases per 463L military pallet, 18 when stacked!
- Four extra-deep base-to-lid locking cleats ensure maximum stacking stability
- Optional Pallet Riser Kit
- Optional Caster Wheel Kit complete with brakes
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- Reinforced honeycomb deck and lid for added strength
- O-ring seal for dust and water resistant seal (IP55)
- Dual Integrated Automatic Pressure Equalization Valves
- Lifetime Guarantee of Excellence
- Stainless steel hardware and padlock protectors
- Locking metal Lidstays keep lid locked in open position
- Store documents outside the case with our Document Container
- **Built to move: by forklift, by wheel or by hand**



CONFIGURATIONS



0550
Standard



0550NF
No Foam

DIMENSIONS

Interior (L x W x D)	47.57 x 24.07" x 17.68 (120.8 x 61.1 x 44.9 cm)
Exterior (L x W x D)	51.05 x 27.54" x 22.79 (129.7 x 70 x 57.9 cm)
Lid Depth	3.19" (8.1 cm)
Bottom Depth	14.49" (36.8 cm)
Total Depth	17.68" (44.9 cm)
Int Volume	11.72 ft ³ (0.332 m ³)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

■ Black

WEIGHT

Weight With Foam	95.00 lbs (43.1 kg)
Weight Empty	79.20 lbs (35.9 kg)
Buoyancy	820.00 lbs (371.9 kg)
Master Pack Weight	95.00 lbs (43.1 kg)

TEMPERATURE

Minimum Temperature	-40°
Maximum Temperature	210°

CERTIFICATIONS

IP57

FOAM PROPERTIES

Layer 1 (Lid)	3.20" Convolute
Layer 2 (Base)	0.50" Pad
Layer 3 (Base)	3.50" Pick N Pluck
Layer 4 (Base)	3.50" Pick N Pluck
Layer 5 (Base)	3.50" Pick N Pluck
Layer 6 (Base)	3.50" Pick N Pluck

OTHER

Master Pack	1
--------------------	---

ACCESSORIES



0507
Caster Wheel Kit



0508
Pallet Riser Kit



0551
6 pc. Replacement Foam Set



1630DC
Document Container Accessory

QueenslandCase

3/13 Veronica Street, Capalaba, Brisbane, Qld 4157
Tel. 07-3245 2699
Email: sales@qldcase.com.au
Web: www.qldcase.com.au