



1700

Protector

Long Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Watertight, crushproof, and dustproof**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Fold down side handle
- **Strong polyurethane wheels with stainless steel bearings**
- Stainless steel hardware and padlock protectors
- 3-piece foam set



CONFIGURATIONS



1700
Standard



1700NF
No Foam

DIMENSIONS

Interior (L x W x D)	35.75 x 13.50" x 5.25 (90.8 x 34.3 x 13.3 cm)
Exterior (L x W x D)	38.12 x 16.00" x 6.12 (96.8 x 40.6 x 15.5 cm)
Lid Depth	1.75" (4.4 cm)
Bottom Depth	3.50" (8.9 cm)
Total Depth	5.25" (13.3 cm)
Int Volume	1.47 ft ³ (0.042 m ³)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

 Black	 OD Green	 Desert Tan
---	--	--

WEIGHT

Weight With Foam	16.98 lbs (7.7 kg)
Weight Empty	16.09 lbs (7.3 kg)
Buoyancy	136.91 lbs (62.1 kg)
Master Pack Weight	19.10 lbs (8.7 kg)

TEMPERATURE

Minimum Temperature	-40°
Maximum Temperature	210°

CERTIFICATIONS

IP67
MIL C-4150J
Def Stan 81-41
STANAG 4280


FOAM PROPERTIES

Layer 1 (Lid)	1.63" Pad
Layer 2 (Base)	1.63" Pad
Layer 3 (Base)	1.63" Pad

OTHER

Wheels	2
Master Pack	1
Military	yes

ACCESSORIES



1701
3 pc. Replacement Foam Set



1703
Replacement O-ring



3/13 Veronica Street, Capalaba, Brisbane, Qld 4157
Tel: 07-3245 2699
Email: sales@qldcase.com.au
Web: www.qldcase.com.au