



SUPER-V-SERIES-3U

Super V 3U

- High-strength steel rack frame supports equipment from 10 - 50 kg
- Designed to meet the requirements of Def Stan 81-41 Level J, Mil Standard 810, STANAG 4340 and other European standards.
- Designed to meet ANSI/EIA-310-C for universal rack mounting hole pattern
- 10 different models, frame heights 4-12U in two depths, 480 and 610mm
- Fixed square hole frame for universal equipment fit
- 2" Front Lid, 5" Rear Lid
- Molded in rear edge casters with handles on the lid for ease of movement
- Comfort Grip plastic handles
- Lid Hangers for lid storage while in use
- Anti-reflective black hardware
- Coupling catches for secure stacking
- Sealed gasket and PRV keeps container watertight and eliminates over pressurization
- Choice of SAE 10-32 or Metric M6 clip nuts for even more flexibility in mounting equipment
- REACH and RoHs compliant
- **View our rack mount case micro site for more details**
- Case shock mounts provide protection from drops and vibration



DIMENSIONS

| | |
|--------------------------------|--|
| Exterior (L x W x D) | 38.50 x 28.30" x 11.40 (97.8 x 71.9 x 29 cm) |
| Rack Height | 5.25" (13.3 cm) |
| Rack Depth | 24.00" (61 cm) |
| Interior Lid Depth | 2.20" (5.6 cm) |
| Interior Back Lid Depth | 5.20" (13.2 cm) |

MATERIALS

| | |
|-------------------|---|
| Body | RotoMolded Polyethylene |
| O-Ring | Silicone Sponge |
| Purge Body | Aluminum |
| Hardware | Stainless Steel (Black Oxide) / RoHs Nickel Black |
| Frame | Steel (Clear Coated) |

COLOURS

- Black

WEIGHT

| | |
|---------------|---------------------|
| Weight | 50.00 lbs (22.7 kg) |
|---------------|---------------------|



3/13 Veronica Street, Capalaba, Brisbane, Qld 4157
Tel. 07-3245 2699
Email: sales@qldcase.com.au
Web: www.qldcase.com.au