



## iM2975

### Storm Travel Case

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

- Five Press & Pull Latches
- Two Integrated Key Lockable Latches
- Two Double-layered, Soft-grip Handles
- O-ring seal
- Specialized molded foam interior designed for Pump or Semi-automatic shotguns and accessories
- Powerful Hinges
- Two stainless steel padlock protectors
- Retention Strap Instructions
- Two Padlockable Hasps
- Guaranteed For Life



### CONFIGURATIONS



**iM2975**  
Standard



**iM2975-X0000**  
No Foam



**iM2975-X0002**  
With Padded Dividers

### DIMENSIONS

<b>Interior (L x W x D)</b>	29.00 x 18.00" x 13.80 (73.7 x 45.7 x 35.1 cm)
<b>Exterior (L x W x D)</b>	31.30 x 20.40" x 15.50 (79.5 x 51.8 x 39.4 cm)
<b>Lid Depth</b>	2.00" (5.1 cm)
<b>Bottom Depth</b>	11.80" (30 cm)
<b>Total Depth</b>	13.8" (35.1 cm)
<b>Int Volume</b>	4.17 ft <sup>3</sup> (0.118 m <sup>3</sup> )

### MATERIALS

<b>Body</b>	Injection Molded HPX® high performance resin
<b>Latch</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Latch (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>O-Ring</b>	EPDM
<b>Pins</b>	Stainless Steel
<b>Pins (Alt)</b>	Aluminum
<b>Foam</b>	1.3/1.35 polyester
<b>Purge Body</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Purge Body (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>Purge Vent</b>	Gortex membrane

### COLOURS

<span style="display: inline-block; width: 10px; height: 10px; background-color: black; margin-right: 5px;"></span> Black	<span style="display: inline-block; width: 10px; height: 10px; background-color: #556b2f; margin-right: 5px;"></span> OD Green
---	--

## WEIGHT

<b>Weight With Foam</b>	29.50 lbs (13.4 kg)
<b>Weight Empty</b>	22.80 lbs (10.3 kg)
<b>Buoyancy</b>	250.02 lbs (113.4 kg)
<b>Master Pack Weight</b>	31.50 lbs (14.3 kg)

## TEMPERATURE

<b>Minimum Temperature</b>	-20°
<b>Maximum Temperature</b>	140°

## CERTIFICATIONS

MIL-STD-810F  
ATA 300  
FED-STD-101C

## FOAM PROPERTIES

<b>Layer 1 (Lid)</b>	2.00" Convolute
<b>Layer 2 (Base)</b>	0.63" Pad
<b>Layer 3 (Base)</b>	1.88" Pick N Pluck
<b>Layer 4 (Base)</b>	1.88" Pick N Pluck
<b>Layer 5 (Base)</b>	1.88" Pick N Pluck
<b>Layer 6 (Base)</b>	1.88" Pick N Pluck
<b>Layer 7 (Base)</b>	1.88" Pick N Pluck
<b>Layer 8 (Base)</b>	1.88" Pick N Pluck

## OTHER

<b>Extendable Handle</b>	yes
<b>Master Pack</b>	1
<b>Military</b>	yes

---


## ACCESSORIES




**iM29XX-UTILITYORG**  
Utility Organizer



**iM29XX-BEZEL-LID**  
Lid Bezel Kit



**iM29XX-BEZEL**  
Base Bezel Kit



**iM2975-FOAM**  
8 pc. Replacement Foam Set



**iM2975-DIV**  
Padded Divider Set



**iM-VALVE-M-B**  
Manual Purge Valve



**iM-LIDSTAY**  
Lid Stay

---

**Queensland Case**

3/13 Veronica Street, Capalaba, Brisbane, Qld 4157  
Tel. 07-3245 2699  
Email: sales@qldcase.com.au  
Web: www.qldcase.com.au